

# Calibrated Okume-Faced Ply for Clean Interior Fabrication.

IMPLY OG plywood is specified for practical interiors where construction, manufacturing process, and application suitability need to be clear before selection.

<b>+/- 0.1 mm indicative calibration tolerance</b> Calibration	<b>4 Press Core Composed</b> Manufacturing	<b>20-Year</b> Limited Warranty
---	---	------------------------------------

## Technical Specifications

Sub Title	OG
Face Material	Okume
Core	Mixed Hardwood
Manufacturing Process	4 Press Core Composed
Calibrated	Yes
Commercial Ply	Yes
Waterproof Ply	No
Available Thickness	6 / 9 / 12 / 19 mm
Available Sizes	8x4 ft / 7x4 ft
Density (Avg.) *	650-750 kg/m <sup>3</sup>
Moisture Content *	8-12%
Screw Holding Strength *	> 1100 N

## Performance Advantages

<b>Calibrated Finish</b>	Uniform thickness improves lamination and assembly consistency.
<b>Composed Core</b>	4 Press Core Composed construction improves panel stability.
<b>Interior Versatility</b>	Useful across dry-area furniture and fit-out applications.

## Testing & Construction Parameters

BWR / BWP Resistance *	As applicable by product grade and final lab confirmation
Glue Type (MR)	Urea Formaldehyde
Glue Type (BWR/BWP)	Phenol Formaldehyde
Termite Treatment	Chemical Dip Treated
Thickness Variants	6 / 9 / 12 / 19 mm
Ply Construction Matrix *	6mm: 5 Plies 9mm: 7 Plies 12mm: 9 Plies 16mm: 11 Plies 19mm: 13 Plies

## Recommended Applications

Wardrobes
TV units
Shelving
Wall paneling
Office furniture
Retail shop-fit elements

## Warranty Summary

IMPLY offers a 20-Year Limited Warranty against termite, borer attack and manufacturing defects, subject to recommended storage, installation and usage conditions.

Architect & Dealer Support - Bangalore

info@imply.co.in | www.imply.co.in

\*Marked values are indicative placeholders pending final lab confirmation.