

# Reliable Commercial Plywood for Everyday Interior Builds.

IMPLY Plus plywood is specified for practical interiors where construction, manufacturing process, and application suitability need to be clear before selection.

<b>Standard commercial tolerance</b> Calibration	<b>Manual</b> Manufacturing	<b>20-Year</b> Limited Warranty
---	--------------------------------	------------------------------------

## Technical Specifications

Sub Title	Plus
Face Material	Gurjan
Core	Neem
Manufacturing Process	Manual
Calibrated	No
Commercial Ply	Yes
Waterproof Ply	BWR
Available Thickness	6 / 9 / 12 / 16 / 19 mm
Available Sizes	8x4 ft / 7x4 ft
Density (Avg.) *	650-750 kg/m <sup>3</sup>
Moisture Content *	8-12%
Screw Holding Strength *	> 1100 N

## Performance Advantages

<b>Practical Strength</b>	Neem core construction supports dependable interior usage.
<b>BWR Protection</b>	Suited to commercial work where basic water resistance is preferred.
<b>Site Friendly</b>	Available in multiple thicknesses for regular carpentry needs.

## Testing & Construction Parameters

BWR / BWP Resistance *	As applicable by product grade and final lab confirmation
Glue Type (MR)	Urea Formaldehyde
Glue Type (BWR/BWP)	Phenol Formaldehyde
Termite Treatment	Chemical Dip Treated
Thickness Variants	6 / 9 / 12 / 16 / 19 mm
Ply Construction Matrix *	6mm: 5 Plies 9mm: 7 Plies 12mm: 9 Plies 16mm: 11 Plies 19mm: 13 Plies

## Recommended Applications

Furniture carcasses
Storage units
Wall backing
Partitions
Counters and site-built interiors
General commercial interior work

## Warranty Summary

IMPLY offers a 20-Year Limited Warranty against termite, borer attack and manufacturing defects, subject to recommended storage, installation and usage conditions.

Architect & Dealer Support - Bangalore

info@imply.co.in | www.imply.co.in

\*Marked values are indicative placeholders pending final lab confirmation.